

SHEET FEEDING DEVICE FOR AN IMAGE FORMING APPARATUS

BACKGROUND OF THE INVENTION

The present invention relates to a sheet feeding device for an image forming apparatus and more particularly to a sheet feeding device built in or operatively connected to a printer, copier or similar image forming apparatus.

A stencil printer belonging to a family of printers includes a print drum around which a master is wrapped. A press roller, press drum or similar pressing means presses a sheet fed from a sheet feeding device at a preselected timing against the master. As a result, ink is transferred from the inside of the print drum to the sheet via the perforations of the master, forming an ink image on the sheet. In a copier, for example, a toner image is transferred from an image carrier to a sheet fed from a sheet feeding device at a preselected timing.

The sheet feeding device is built in or operatively connected to the image forming apparatus and includes a tray or a cassette loaded with a stack of sheets. A pickup roller contacts the top sheet and pays it out. A separator pad or separating member and a separator roller cooperate to separate the top sheet being paid out by the pickup roller from the underlying sheets. This kind of sheet separation,

generally referred to as a friction separation system, causes a greater frictional force to act between the separator pad and the sheets than between the sheets.

A stencil printer, among others, is operated with various kinds of sheets. Sheets are generally classified into standard sheets, thin sheets and thick sheets or more minutely into standard sheets, rough sheets, thin sheets, thick sheets, and special sheets. As for the minute classification, standard sheets include high quality sheets (high quality 55 kg sheets, high quality sheets for stencil printers and so forth), medium quality sheets, and recycled sheets. Thin sheets include thin *Noshigami* (a piece of paper customarily attached to a gift in Japan) and high quality 45 kg sheets. Thick sheets include high quality 135 kg sheets or above, drawing paper, and postcards. Special sheets include rectangular envelopes.

Sheets of each kind or each size have particular quality including thickness and surface condition and a particular weight. Therefore, the frictional force depends on the kind and size of sheets and sometimes renders sheet separating conditions inadequate. This is apt to cause a plurality of sheets to be fed at the same time (overlap feed hereinafter) or cause no sheets to be fed (feed failure hereinafter) or cause thick sheets to peel off, proving that the optimal sheet feed conditions including a feed pressure and a separation pressure depend on the kind and size of sheets.

As for a stencil printer operable with various kinds of sheets, as stated above, it is difficult to optimize sheet feed conditions

for all kinds of sheets by simply adjusting the feed pressure, separation pressure and so forth stepwise with a single separator pad or a single pad angle.

Generally, the sheet feed conditions become inadequate and
5 bring about defective sheet feed, depending also on temperature, humidity and other environmental conditions. For example, when temperature or humidity drops, the overlap feed is apt to occur. In light of this, a high separation pressure and a low feed pressure are selected. When temperature or humidity high, a low separation
10 pressure and a high feed pressure are selected because the feed failure is apt to occur.

On the other hand, for a given separation pressure, the frictional force to act and therefore the sheet feeding ability depends on the material and surface condition of the separator pad.
15 It is therefore a common practice to classify sheets by kind and size and prepare a plurality of different separator pads each matching with a particular class of sheets as determined by experiments. An optimal separator pad is selected in accordance with the kind and size of sheets to be used.

20 However, in most of conventional sheet feeding devices, the materials of the separator pads and pad angles are fixed and cannot be switched. As a result, when the sheet feeding device is frequently operated, i. e., when a great number of sheets are fed, the separator pads must be frequently replaced due to wear. The kind of the
25 separator pad and pad angle, if switchable, are switched by hand.

Manual switching operation is not easy and is therefore extremely troublesome to perform.

The above problems with the conventional sheet feeding devices may be summarized, as follows.

5 (1) The kind of the separator pad and pad angle which cannot be automatically switched are troublesome to replace. It is therefore impractical to set up optimal sheet feed conditions matching with the kind of sheets to be used or temperature, humidity and other environmental conditions, resulting in jams, overlap feed,
10 peeling and other defective sheet feed.

 (2) The kind of the separator pad and pad angle, if switchable, cannot be easily switched. This, coupled with the fact that the switching operation relies on the operator's experiences, makes it difficult to select optimal sheet feed conditions. Further,
15 although the kind of the separator pad and pad angle may be variable in accordance with the kind and size of sheets, the operation for varying the sheet feed conditions is extremely troublesome and delicate to perform. As a result, printing, for example, is often
20 executed without the optimization of the sheet feed conditions, again resulting in defective sheet feed. This prevents merits achievable with the switching of the kind of the separator pad and pad angle from being made most of.

 (3) When spare pads are not available at the time for replacing the separator pad in use, a long period of time is necessary for
25 replacement, or the apparatus is killed over a long period of time

to simply wait for the delivery of spare pads.

Technologies relating to the present invention are disclosed in, e.g., Japanese Patent Laid-Open Publication Nos. 5-229243, 9-30714, 9-235033, 7-125855, 8-108947, 8-301500, 9-86692, 9-208058 and
5 10-139191, U.S. Patent No. 5,927,703, and U.S. Patent Application
Serial Nos. 08/925,648, 09/222,820, and 09/135,856.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide
10 a sheet feeding device for an image forming apparatus capable of
automatically switching the kind of a separator pad and/or a pad angle
without any troublesome manual operation.

It is another object of the present invention to provide a
sheet feeding device for an image forming apparatus capable of
15 automatically switching a separating member and/or the angle of the
separating member in accordance with the kind of sheets to be used
and temperature, humidity and other environmental conditions.

It is still another object of the present invention to provide
a sheet feeding device for an image forming apparatus capable of
20 automatically selecting and setting optimal sheet feed conditions
matching with the kind of a separating member and/or the angle of the
separating member automatically selected, thereby guaranteeing
optimal sheet feed conditions at all times.

It is a further object of the present invention to provide a
25 sheet feeding device for an image forming apparatus obviating an

occurrence that a long period of time is wasted for replacement due to the absence of spare pads or that the apparatus is killed over a long period of time due to the absence of spare pads.

5 In accordance with the present invention, a sheet feeding device for an image forming apparatus includes a plurality of separating members each having a particular coefficient of friction with respect to a sheet for separating sheets one by one, and an automatic separating member switching mechanism for automatically selecting one of the separating members.

10 Also, in accordance with the present invention, a sheet feeding device for an image forming apparatus includes a plurality of separating members for separating sheets one by one, and an automatic separation angle switching mechanism for automatically switching an angle of the separating members.

15 Further, in accordance with the present invention, a sheet feeding device for an image forming apparatus includes a plurality of separating members having the same coefficient of friction with respect to sheets for separating the sheets one by one, an automatic separating member switching mechanism including a drive source for
20 automatically replacing the separating members, a counter for counting the sheets fed, and a controller for so controlling, when the counter counts a preselected number of sheets, the drive source as to automatically replace one separating member in use with another separating member.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description taken with the accompanying drawings in which:

5 FIG. 1 is a front view showing a stencil printer to which a sheet feeding device embodying the present invention is applied;

 FIG. 2A is a side elevation of a sheet separating section included in the illustrative embodiment, as seen from the sheet discharge side;

10 FIG. 2B is a front view of the sheet separating section.

 FIG. 3 is an enlarged view of separator pads included in the sheet separating section together with members around them, as seen in a direction indicated by an arrow D in FIG. 2B;

 FIG. 4A is a front view of one of the separator pads;

15 FIG. 4B is a section showing a pad holder from which a pad is removed;

 FIG. 5 is an enlarged view of the separator pads and members around them;

20 FIG. 6 is a front view showing one separator pad and a pad sensor;

 FIG. 7 is a partly taken away isometric view showing a sheet size sensing mechanism included in the illustrative embodiment together with a tray;

25 FIG. 8 is a fragmentary plan view showing an operation panel included in the stencil printer;

FIG. 9 is a fragmentary plan view showing a specific picture appearing on an LCD included in the operation panel together with keys adjoining the LCD;

5 FIG. 10 is a fragmentary plan view showing another specific picture appearing on the LCD;

FIG. 11 is a block diagram schematically showing a control system included in the stencil printer;

FIG. 12 is a table listing specific sheet feed conditions unique to the illustrative embodiment;

10 FIG. 13 is a fragmentary front view showing an alternative embodiment of the present invention;

FIG. 14 is a fragmentary section for describing how a sheet clamper included in the alternative embodiment selectively clamps a sheet and the resulting sheet conveying operation; and

15 FIG. 15 is a table listing specific sheet feed conditions unique to the alternative embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the sheet feeding device in accordance with the present invention will be described hereinafter. An image forming apparatus to which the illustrative embodiments are applied is implemented as a stencil printer by way of example. It is to be noted that a term "sheet feed conditions" to appear repeatedly hereinafter include not only conditions for conveying a sheet toward
20 an image forming section (including a printing section) but also
25

conditions for conveying it away from the image forming section after image formation.

Referring to FIG. 1 of the drawings, a stencil printer, generally 200, includes a cylindrical, porous print drum 51 for wrapping a master or cut stencil 53 therearound. A master discharging section 230 is located at the left-hand side of the print drum 51, as viewed in FIG. 1, for peeling off the used master 53 wrapped around the drum 51 and storing it. A master making section 220 is located at the right-hand side of the print drum 51, as viewed in FIG. 1, for making the master 53 while conveying it. A document scanning section 210 is positioned above the master discharging section 230, print drum 51 and master making section 220 for reading a document. An ink feeding device, not shown, is arranged in the print drum 51 for feeding ink to the master 53 wrapped around the drum 51. A press roller or pressing means 80 is positioned below the print drum 51 for pressing a sheet 56 against the print drum 51. A sheet feeding section 240 is located at the right-hand side of the press roller 80, as viewed in FIG. 1, and includes a sheet feeding device embodying the present invention for feeding the sheet 56 toward a print position between the print drum 51 and the press roller 80. A sheet discharging section 260 is located at the left-hand side of the print drum 51 and press roller 80, as viewed in FIG. 1. The print drum 51, ink feeding device and press roller 80 constitute a printing section 250.

The sheet discharging section 230, master making section 220

and document scanning section 210 may be arranged as shown in, e.g., FIG. 8 of previously mentioned Laid-Open Publication No. 5-229243 and will not be described specifically.

5 A clamber 52 is positioned on part of the outer periphery of the print drum 51 for clamping the leading edge of the master 53 fed from the master making section 220. When the print drum 51 is rotated in a direction indicated by an arrow in FIG. 1, the master 53 clamped by the clamber 52 is sequentially wrapped around the drum 51.

10 The sheet feeding section 240 includes a tray 54, a pickup roller portion 32, a separating portion 31, and a pair of registration rollers 81 and 82. The tray 54 is loaded with a stack of sheets 56 and movable up and down. As shown in FIG. 7, a pair of side fences 55 are mounted on the tray 54 and movable toward and away from each other in a direction Y perpendicular to a direction X in which the
15 sheets 56 are fed from the tray 54. The direction Y is the widthwise direction of the sheets 56. The side fences 55 are interlocked to each other and used to position the widthwise edges of the sheets 56 in accordance with the sheet size.

A sheet size sensing mechanism is arranged on the bottom of
20 the tray 54 and includes sheet size sensing means responsive to the size of the sheets 56. The sheet size sensing mechanism determines the size of the sheets 56 in interlocked relation to the movement of the side fences 55 in the direction Y. Specifically, as shown in FIG. 7, the sheet size sensing mechanism includes the side fences 55, a
25 pinion 79, racks 78 and 77, a screen 77a, and size sensors 57a, 57b

and 58. The pinion 79 is rotatably mounted on a stationary member positioned on the underside of the tray 54. The rack 78 is formed at the edge of the lower portion of the left side fence 55, as viewed in FIG. 7. The rack 77 is formed at the edge of the lower portion of the right side fence 55, as viewed in FIG. 7. The racks 78 and 77 are held in mesh with the pinion 79 while facing each other. The screen 77a protrudes downward from the lower portion of the right side fence 55 and includes a plurality of notches spaced from each other by a suitable distance. The size sensors 57a and 57b are affixed to the above stationary member at a suitable distance from each other. The screen 77a selectively meets the size sensors 57a and 57b. The size sensor 58 is also affixed to the stationary member and spaced by a suitable distance in the direction X.

The size sensors 57a and 57b each are a transmission type optical sensors made up of a light emitting portion and a light receiving portion. The size sensors 57a and 57b determine the size of the sheets 56 in the direction Y when the screen 77a selectively obstruct their optical paths. The size sensor 58 is a reflection type optical sensor made up of a light emitting portion and a light receiving portion and senses the size of the sheets 56 in the direction X. The size sensors 57a, 57b and 58 constitute a size sensor group 57A playing the role of the sheet size sensing means. A CPU (Central Processing Unit), which will be described later, combines data output from the size sensor group 57A to thereby determine the size of the sheets 56.

For details of the above sheet size sensing system, reference may be made to previously mentioned Laid-Open Publication No. 9-30714 by way of example. Of course, such a sheet size sensing system is only illustrative. While the sheet size sensing mechanism has been shown and described as including only a limited number of sensors for the simplicity of description, additional sensors may advantageously be used to automatically sense even postcards, envelopes and legal size sheets. This is particularly true with a stencil printer using various kinds of sheets, as stated earlier.

As shown in FIGS. 1 and 7, a sheet sensor for determining whether or not the sheets 56 are present is mounted on the stationary member of the tray 54 and implemented by a reflection type optical sensor.

A tray motor 59 causes the tray 54 to move up and down along guide means, not shown, via a pinion 61 and a rack 60 meshing with the pinion 61. The pinion 61 is affixed to the output shaft of the tray motor 59. The motor 59 may be implemented by a stepping motor by way of example.

The pickup roller portion 32 positioned above the tray 54 includes a pickup roller or sheet feeding means 62, a separator roller 63, and a feed pressure adjusting mechanism. The pickup roller 62 sequentially pays out the sheets 56 stacked on the tray 54, the top sheet being first. The separator roller 63 cooperates with either one of separator pads 1 and 2, which will be described, to separate the top sheet 56 from the underlying sheets 56. The feed pressure

adjusting mechanism adjusts a feed pressure to act on the sheet 56.

The separator roller 63 is mounted on a shaft 65 that is, in turn, supported by an apparatus frame 76. A sheet feed motor 66 is located in the vicinity of the shaft 65 for driving the separator roller 63 and implemented by a stepping motor. The sheet feed motor 66 drives the shaft 65 via a timing belt 67. The timing belt 67 is passed over a drive pulley mounted on the output shaft of the motor 66 and a double, driven pulley mounted on the shaft 65.

An arm 68 is rotatable about the axis of the shaft 65 at one end thereof. The pickup roller 62 is rotatably mounted on the other end of the arm 68 via a shaft 69 and angularly movable up and down about the shaft 65 together with the arm 68. A timing belt 70 is passed over the double, driven pulley mounted on the shaft 65 and a pulley mounted on the shaft 69 of the pickup roller 62. The pickup roller 62 is therefore driven by the sheet feed motor 66 at the same time as the separator roller 63.

An upper limit sensor 71 is mounted on the apparatus frame 76 above the tray 54 for sensing the upper limit position of the top of the sheet stack 56. Specifically, when the top of the arm 68 contacts a feeler 71a included in the upper limit sensor 71, the sensor 71 determines that the top of the sheet stack 56 has reached its upper limit position. A lower limit sensor 94 is positioned below the tray 54.

The feed pressure adjusting mechanism is positioned above, but in the vicinity of, the separator roller 63. Specifically, a tension

spring or feed pressure source 72 is anchored to the arm 68 at one end thereof. A slider 73 includes a rack 73a and is guided by guide means, not shown, in the up-and-down direction. A feed pressure motor 75 is implemented by a stepping motor for causing the slider 73 to move up and down. A pinion gear 74 is mounted on the output shaft of the feed pressure motor 75 and held in mesh with the rack 73a. A feed pressure position sensor 36 shown only in FIG. 11 senses the displacement of the slider 73.

The bias of the tension spring 72 causes a moment of rotation to act on the pickup roller 62 via the arm 68, so that a feed pressure is generated. When the feed pressure motor 75 is driven to move the slider 73 upward, as viewed in FIG. 1, the tension spring 72 is stretched to increase its bias and therefore the feed pressure. It is therefore possible to adjust the feed pressure stepwise by driving the motor 75.

The feed pressure position sensor 36 senses the displacement of the slider 73 with a configuration similar to, e.g., a position sensing board 52 included in a feed pressure adjusting mechanism 22 shown in FIG. 2 of previously mentioned Laid-Open Publication No. 9-235033.

As shown in FIGS. 2A and 2B, the separating portion 31 includes a plurality of separator pads 1 and 2 each having a particular coefficient of friction with respect to the sheets 56. The separating portion 31 is generally made up of a pad switching section C, a pad angle switching section B, and a pad pressure switching

section A. The pad switching section C includes an automatic pad switching mechanism for automatically selecting one of the pads 1 and 2. The pad angle switching mechanism B includes an automatic separation angle switching mechanism for automatically switching the angle of the pad 1 or 2. The pad pressure switching mechanism A includes a separation pressure adjusting mechanism for adjusting the separation pressure of the pad 1 or 2. The pad pressure switching section A is constructed into a unit that is easy to assemble and disassemble. The pad switching section C and pad angle switching section B are also easy to assemble and disassemble. The pad switching section C includes the pad angle switching section B and pad pressure switching section A. The pad angle switching section B includes the pad pressure switching section A. The pad 1 or 2 and the separator roller 63 constitute separating means for separating the top sheet 56 from the underlying sheets 56.

A temperature sensor 38 and a humidity sensor 39 shown only in FIG. 11 are arranged in the vicinity of the separating portion 31 and pickup roller portion 32. The temperature sensor 38 and humidity sensor 39 are respectively responsive to temperature and humidity around the separating portion 31.

More specifically, the pad pressure switching section A includes a pair of pad holder guides or separator guide means 3 each for allowing one of the separator pads 1 and 2 to slide up and down therealong. The pad holder guides 3 are affixed to an angle varying member or moving means 12 which varies the angle of the pads 1 and

2. The separator pads 1 and 2 are held by holders 1b and 2b, respectively. Two compression springs or separation pressure sources 4 are respectively anchored to the holders 1b and 2b at one end thereof and to a press plate 5 at the other end thereof. The press plate 5 is supported by two stepped screws 6 in such a manner as to be movable up and down and includes a rack 5b. A pinion gear 11 is rotatably supported by the angle varying member 12 and held in mesh with the rack 5b. A worm wheel 10 is mounted on the same shaft as the pinion gear 11. A worm 9 is held in mesh with the worm wheel 10. A separation pressure motor 7 is affixed to the angle varying member 12 and includes an output shaft 7a on which the worm 9 is mounted. A separation pressure position sensor group 8 has five separation pressure position sensors 8a, 8b, 8c, 8d and 8e for sensing the displacement of the press plate 5.

15 The separator pads 1 and 2 serve as separating members for surely separating the sheets 56 one by one. Assume that the apparatus is operable with five different kinds of sheets, i. e., standard sheets, rough sheets, thin sheets, thick sheets and special sheets, as stated in relation to the prior art. Then, in the illustrative embodiment, 20 the separator pads 1 and 2 are respectively assigned to standard sheets and special sheets by way of example.

 As shown in FIGS. 2A, 2B, 3, 4A and 4B, the separator pads 1 and 2 respectively include pads 1a and 2a in addition to the holders 1b and 2b to which the pads 1a and 2a are adhered. The pads 1a and 2a each exert a friction force on the sheets 56. The pads 1a and 2a

each have a particular coefficient friction. The pad 1a is assigned to standard sheets 56 and formed of ethylene-propylene rubber (EDPM), urethane or similar material having a relatively great coefficient of friction μ ranging from 1.1 to 1.2. The other pad 2a is assigned to special sheets or thick sheets and formed of urethane, EPDM or similar material having a coefficient of friction μ of 0.8 to 1.0.

As shown in FIGS. 4A and 4B in detail, the holders 1b and 2b each are a hollow molding of, e.g., polyacetal resin (POM), polyamide resin (PA) or similar synthetic resin. Ribs 1c and 2c are respectively formed in the inside of the holders 1b and 2b and serve as seats for the compression springs 4. The holders 1b and 2b may, of course, be implemented by die castings of aluminum or similar metal.

The separating member switching mechanism mentioned earlier automatically replaces one of the separator pads 1 and 2 with the other. As shown in FIG. 6, pad sensors or separating member sensing means 41 are respectively positioned below the separator pads 1 and 2 for identifying the kinds of the pads 1 and 2. When the separator pads 1 and 2 are located at positions shown in FIG. 5 by way of example, the pad sensors 41 are respectively positioned at the left of the pad holder guides 3 slidably accommodating the holders 1b and 2b. The pad sensors 41 are implemented by reflection type optical sensors. As shown in FIG. 5, the pad holder guides 3 each are formed with a window 3a aligning with associated one of the pad sensors 41.

As shown in FIGS. 4 and 5, a notch 42 is formed in the left

side wall of the holder 1b holding the standard separator pad 1 while such a notch is not formed in the other holder 2b holding the special separator pad 2. Therefore, the pad sensor 41 turns on when it does not sense the notch 42 or turns off when it senses the notch 42. A controller, which will be described later, is capable of determining the kinds of the reflector pads 1 and 2 on the basis of the outputs of the pad sensors 41. When three or more separator pads are used, they may be distinguished by the number of notches 42 while the number of pad sensors 41 may be equal to the maximum number of notches 42.

The above notch 42 for distinguishing the pads 1 and 2 may be replaced with an aperture or with black and white or similar colors respectively provided on the tops of the holders 1b and 2b. In such a color scheme, the pad sensors 41 each receive a particular amount of reflection from the associated holder 1b or 2b due to a difference in reflectance between the colors, so that the controller can distinguish the pads 1 and 2 on the basis of the output levels of the sensors 41. If desired, the holders 1b and 2b each may have its entire surfaces or only its top surface or even only its portion to be illuminated by the pad sensor 41 colored.

The angle varying member 12 has a box-like configuration. As shown in FIG. 2A, this member 12 has a recess 12a for mounting the bottoms of the pad holder guides 3. A screen piece 12b protrudes from the left side wall of the lower portion of the member 12.

The press plate 5 is generally inverted L-shaped as seen in a side elevation and formed with a slot 5a elongate in the up-and-down

direction. The previously mentioned two stepped screws 6 are driven into the angle varying member 12 via the slot 5a. In this condition, the stepped screws 6 and slot 5a constitute guide means for slidably guiding the press plate 5 in the up-and-down direction.

5 The separation pressure motor 7 is implemented by a stepping motor and plays the role of separation pressure variation drive means. The separation pressure position sensors 8a through 8e each are a transmission type optical sensor including a light emitting portion and a light receiving portion. The separation pressure position
10 sensor group 8 senses the displacement of the press plate 5 with the sensors 8a through 8e selectively aligning with the screen piece 5c of the press plate 5.

 The separation pressure adjusting mechanism includes the separator pads 1 and 2, compression springs 4, press plate 5, rack
15 5b, pinion gear 11, worm wheel 10, worm 9, separation pressure motor 7 and separation pressure position sensor group 8, as stated previously. Most of the parts constituting the separation pressure adjusting mechanism are mounted on the angle varying member or base
member 12.

20 The separation pressure adjusting mechanism may be regarded as a separation pressure canceling mechanism for automatically canceling the separation pressure acting on the sheets 56 and including the separation pressure motor or separation pressure cancellation drive means 7. Specifically, as shown in FIG. 3, the
25 separator pad 2, for example, usually protrudes from a rectangular

hole 30a formed in a front wall 30 and remains in contact with the separator roller 53 via the sheet stack 56 for generating a separation pressure. Therefore, to automatically replace the separator pad 2 with the separator pad 1, it is necessary to cancel the pressure generating state of the pad 2. More specifically, as shown in FIGS. 2A and 2B, the separation pressure motor 7 lowers the press plate 5 until the top of the pad 2a fully retracts downward from the hole 30a of the front wall 30. This is successful to prevent the pad 2a or the holder 2b from being caught by the edges of the hole 30a, to prevent the pad 2a and separator roller 63 contacting each other from scratching each other, and to prevent the pad 2a and holder 2b from sliding on the rear surface of the front wall 30 and being damaged thereby.

The operation of the separation pressure adjusting mechanism will be described more specifically. Before the operation begins, the separating member switching mechanism automatically selects one of the separator pads 1 and 2. Assume that the mechanism has selected the separator pad 2. Then, the pad 2 protrudes from the hole 30a of the front wall 30 with its top contacting the separator roller 63. The compression spring 4 presses the above pad 2 against the separator roller 63 to thereby generate a separation pressure. When the separation pressure motor 7 is driven, the output torque of the motor 7 is transferred to the rack 5b via the worm 9, wormwheel 10 and pinion gear 11. As a result, the press plate 5 is moved upward, as viewed in FIGS. 2A and 2B, while being guided by the stepped screws 5 and

compressing the compression spring 4. Consequently, the above pressure (compression load) and therefore the separation pressure increases. Conversely, when the motor 7 causes the press plate 5 to move downward, as viewed in FIGS. 2A and 2B, it causes the compression spring 4 to stretch. This reduces the above pressure or compression load and therefore the separation pressure. In this manner, with the motor 7, it is possible to adjust the separation pressure stepwise. For example, with the motor 7 and five separation position sensors 7a-8e, it is possible to adjust the separation pressure in five consecutive steps.

To automatically control the above separation pressure in a greater number of steps, the illustrative embodiment may include a greater number of separation position sensors and control the separation pressure motor 7 in accordance with the outputs of such sensors. The separation pressure position sensor group 8 playing the role of means for sensing the position of the press plate 5 may be replaced with, e.g., a photoencoder mounted on the output shaft of the motor 7 and a single home position sensor responsive to the home position of the press plate. Further, the sensor group 8 may be replaced with only the photoencoder if the motor 7 is capable of being controlled by open loop control.

The pad angle switching section B is made up of the pad pressure switching section A, the angle varying member 12, a sector gear 16, a drive gear 15 meshing with the gear 16, an angle motor 14, and an angle sensor group 17. The angle varying member 12 is angularly

movable about two stepped fulcrum screws 13. The gear 16 is mounted on the lower portion of the right wall of the angle varying member 12, as viewed in FIG. 2A. The angle motor 14 is mounted on a movable member 18 and has the drive gear 15 mounted on its output shaft. The angle sensor group or angle sensing means 12 senses the angle of the separator pad 1 or 2 via the angular displacement of the angle varying member 12.

As shown in FIG. 2A, the upper ends of the movable member 18 spaced from each other in the direction Y are cut and bent to form support portions 18b supporting the opposite ends of the angle varying member 12. In FIG. 2A, portions 18g are the cut portions of the movable member 18. An elongate slot 18a is formed in the lower portion of the movable member 18 in the direction Y so as to guide the movable member 18 in the direction Y. Screen pieces 18e and 18f respectively protrude from the left edge and right edge of the movable member 18 in the direction Y. The right and left end portion of the movable member 18 in the direction Y are bent to form inserting portions 18c and 18d, respectively. A ball screw 20 has a shank portion and a screw portion respectively inserted in the inserting portions 18c and 18d, so that the ball screw 20 is axially movable and rotatable about its axis.

Holes, not shown, are formed in the top right and top left portions of the angle varying member 12. The two stepped fulcrum screws 13 are respectively held in threaded engagement with the support portions 18b and 18b via the above holes of the angle varying

member 12. In this condition, the angle varying member 12 is selectively rotatable clockwise or counterclockwise, as viewed in FIG. 2B, over a preselected angular range.

The angle motor 14 is implemented by a stepping motor and plays
5 the role of drive means for the separation angle switching mechanism. The motor 14 is mounted on the movable member 18 which is, in a sense, the base member of the pad angle switching section B.

The angle sensor group 17 is made up of three angle sensors
10 17a, 17b and 17c responsive to the angular positions of the angle varying member 12. The angle sensors 17a-17c each are an optical sensor having a light emitting portion and a light receiving portion. The screen piece 12b selectively screens the optical path of the angle sensors 17a-17c, indicating the angular position of the angle varying means 12, i.e., the angle of the separator pad 1 or 2.

15 The separation angle switching mechanism is made up of the pad pressure switching portion A, angle varying means 12, stepped fulcrum screws 13, gear 16, drive gear 15, angle motor 14, and angle sensor group 17, as stated previously. The operation of the separation angle switching mechanism will be described more specifically
20 hereinafter.

When the angle motor 14 is driven, its output torque is transferred to the gear 18 via the drive gear 15. As a result, the angle varying member 12 is angularly moved about the fulcrum screws 13 clockwise or counterclockwise over a preselected range. For
25 example, when the member 12 is moved clockwise, as viewed in FIG. 2B,

it increases the angle of the separator pad 2 (pad 2a); when the member 12 is moved counterclockwise, it reduces the angle of the pad 2. At this instant, the angle of the separator pad 2 is determined on the basis of the outputs of the angle sensors 17a-17c which the screen
5 piece 12b of the angle varying member 12 selectively meets. With the motor 14 and three angle sensors 17a-17c, the illustrative embodiment is capable of automatically switching the angle of the separator pad 1 or 2 in three steps.

To automatically control the angle of the separator pad 1 or
10 2 in a greater number of steps, the illustrative embodiment may include a greater number of angle sensors and control the angle motor 7 in accordance with the outputs of such sensors. The angle sensor group 17 playing the role of means for sensing the angle of the angle
15 varying member 12 may be replaced with, e.g., a photoencoder mounted on the output shaft of the motor 14 and a single home position sensor responsive to the home position of the angle varying member 12. Further, the sensor group 17 may be replaced with only the photoencoder if the motor 14 is capable of being controlled by open
loop control.

20 The pad switching section C is made up of the pad pressure switching section A, the pad angle switching section B, a ball nut 19, the ball screw 20, a worm wheel 21, a worm 22, a pad motor 23, and two sensors 25 and 26. The ball nut 19 is affixed to the right bent end of the movable member 118 and held in threaded engagement
25 with the ball screw 20, constituting separating member moving means

for moving the movable member 18 in the direction Y. The worm wheel 21 is affixed to one end of the ball screw 20 and held in mesh with the worm wheel 21. The pad motor 23 is affixed to a base 28 via a bearing member 27b and has the worm 22 on its output shaft. The
5 sensors or switching sensing means 25 and 26 are responsive to the displacement of the movable member 18, i.e., switching between the separator pads 1 and 2.

The base 28 is affixed to a front panel 30 by screws. The bearing member 27b and another bearing member 27a are fastened to the
10 base 28 by screws not shown. The bearing member 27a supports the left end of the ball screw 20 via a stop ring, not shown, such that the ball screw 20 is rotatable, but not movable in the direction Y. Likewise, the bearing member 27b supports the right end of the ball screw 20 via a stop ring, not shown, such that the ball screw 20 is
15 rotatable, but not movable in the direction Y. Two stepped screws 24 are driven into the base 28 via a slot 18a formed in the movable member 18, allowing the member 18 to move in the direction Y in FIG. 2A.

The pad motor 23 is implemented by a stepping motor and serves
20 as drive means for the separation member switching mechanism. The motor 23 is affixed by screws to the base 28 which is, in a sense, the base member of the pad switching section C.

The switching sensors 25 and 26 each are an optical sensor made up of a light emitting portion and a light receiving portion. The
25 screen pieces 18e and 18f each selectively meet the associated sensor

25 or 26, indicating the switched position of the separator pad 1 or 2.

The pad switching mechanism is made up of the pad pressure switching section A, pad angle switching section B, ball nut 19, ball screw 20, worm wheel 21, worm 22, pad motor 23 and sensors 25 and 26, as stated above. The operation of the pad switching mechanism will be described more specifically. When the pad motor 23 is driven, its output torque is transferred to the ball screw 20 (e. g. right-hand thread) via the worm 22 and worm wheel 21. The ball screw 20 causes, in cooperation with the ball nut 19, the pad pressure switching section and pad angle switching section B to move by being guided by the stepped screws 24 in the direction opposite to the direction of movement of the above thread. Consequently, one of the pads 1 and 2 is automatically selected and sensed by the associated switching sensor 25 or 26.

To automatically select a greater number of separator pads at a time, the illustrative embodiment may include a greater number of switching sensors and control the pad motor 23 in accordance with the outputs of such sensors. The switching sensors 25 and 26 playing the role of means for sensing the positions of the movable member 18 may be replaced with, e. g., a photoencoder mounted on the output shaft of the motor 23 and a single home position sensor responsive to the home position of the movable member 18. Further, the sensors 25 and 26 may be replaced with only the photoencoder if the motor 23 is capable of being controlled by open loop control.

While the illustrative embodiment includes all of the separating member switching mechanism, separation angle switching mechanism and separation pressure adjusting mechanism, it may include only one of the separating member switching mechanism and separation angle switching mechanism with or without the separation pressure adjusting mechanism.

Referring again to FIG. 1, the registration rollers 81 and 82 are located upstream of the press roller 80 in the direction X for conveying the sheet 56 toward the print position between the print drum 51 and the press drum 80. A drive mechanism including a registration motor or stepping motor 82A causes each of the registration rollers 81 and 82 to rotate in a particular direction, as indicated by an arrow in FIG. 1. The registration rollers 81 and 82 therefore drive the leading edge of the sheet 56 at a preselected timing matching with the rotation of the print drum 51. Specifically, the lower registration roller 82 is a drive roller having a driven pulley, not shown, mounted on its shaft. A timing belt, not shown, is passed over the driven pulley and a drive pulley, not shown, mounted on the output shaft of the registration motor 82A. The motor 82A causes the registration roller 82 to rotate via the timing belt. A leading edge sensor 83 is positioned upstream of the two rollers 81 and 82 in the direction X for sensing the leading edge of the sheet 56. The leading edge sensor 83 is implemented by a reflection type optical sensor.

An overlap feed sensor or overlap feed sensing means 43 (shown

only in FIG. 11) is located on a sheet path between the leading edge sensor 83 and the separator portion 31 for sensing the simultaneous feed of two or more sheets 56. This sensor 43 may be implemented by, e.g., a transmission type optical sensor capable of sensing the thickness of sheets 56 in terms of the intensity of reflection or a reflection type optical sensor responsive to the level of the quantity of reflection.

A print counter 47 (shown only in FIG. 11) is additionally included in the stencil printer 200 for counting the sheets 56 fed in terms of the sheets 56 subjected to printing. Specifically, a suction unit includes a conveyor belt 85, a suction fan 86 and a sheet discharge sensor not shown. The print counter or counting means 47 counts prints on the basis of the number of times of ON/OFF operations of the sheet discharge sensor. Alternatively, the controller which will be described may count the number of times of ON/OFF operations of the leading edge sensor 83 in order to directly determine the number of sheets fed.

The sheet discharge section 260 includes an air blower 84, a print conveying device, a right and a left jump board 90, and a tray 87. In the print conveying device, the conveyor belt 85 is passed over a front roller 85A and a rear roller 85B while the suction fan 86 is caused to retain a sheet 56a on the belt 85 by suction. This kind of configuration is conventional and will not be described specifically.

The sheet or print 56a carrying an image thereon is peeled off

from the print drum 51 by the air blower 84 and then driven out to the tray 87 by the belt 85 while being sucked by the suction fan 86. The tray 87 has an end fence 88 and a pair of side fences arranged thereon. The end fence 88 stops the leading edge of the print 56a and thereby positions the leading edge and training edge of the print 56a. The side fences 89 position the opposite side edges of the print 56 by guiding them.

The right and left jump boards 90 cause the print 56a being driven out to the tray 87 to bend in the form of a letter U, thereby providing the print 56a with an adequate degree of rigidity. A rack-like slider 91 is anchored at one end to part of each jump board 90 and guided by guide means, not shown, in substantially the up-and-direction.

A jump board motor 93 is located in the vicinity of the slider 91 for moving the slider 91 in the up-and-down direction. A pinion gear 92 is mounted on the output shaft of the jump board motor 93 and held in mesh with a rack 91a included in the slider 91. The jump board motor 93 is implemented by a stepping motor. A jump board angle sensor 37 (shown only in FIG. 11) adjoins the lower end of the slider 91 for sensing the displacement of the slider 91. The jump board angle sensor 37 senses the displacement of the slider 91 with a configuration similar to the feed pressure position sensor 36 and separation pressure position sensor group 8.

As stated above, by driving the jump board motor 93, it is possible to adjust the angle of the jump boards 90 stepwise and

therefore to control the degree of curvature or rigidity of the sheet 56a.

The document scanning section 210 is arranged on the top of the apparatus frame 6. An operation panel 110 shown in FIG. 8 is also
5 mounted on the top of the apparatus frame 76 above the document scanning section 210.

As shown in FIG. 8, the operation panel 110 includes a start key 111 for starting a sequence beginning with printing, including document reading, master discharging, master making and master
10 wrapping, and ending with sheet discharging. Numeral keys 113 are used to input a desired number of prints and other numerical values. A print key 112 causes the number of prints input on the numeral keys 113 to be output when pressed. A proof print key 113A is used to start a proof printing operation. An LCD (Liquid Crystal Display) or
15 display means 114 displays operation statuses, messages, functions selected and so forth as well as guidance for the selection of desired functions, as needed. Four select keys 115 are respectively positioned below four items "Kind of Document (Doc)", "Magnification (Mag) Change", "King of Sheets" and "Position Adjustment (Adj)"
20 appearing in four elongate frames at the bottom of the LCD 114. Four scroll keys 123c, 123a, 123b and 123d (123 collectively) are used to select a desired function in any one of four different directions. In FIG. 8, a print mode picture for a usual basic operation is shown as appearing on the LCD 114. When an initial set key 122 is pressed,
25 the LCD 114 replaces the print mode picture with an initial set mode

picture or menu picture for allowing the operator to change the initial values of various functions or to set operating conditions in accordance with desired conditions of use.

5 The proof print key 113A causes a single proof print to be output when pressed once or causes a plurality of proof prints to be output when continuously pressed.

10 The controller, which will be described, controls the LCD 114 via an LCD driver included in an LCD device, not shown. As for the select keys 115, the leftmost key, as viewed in FIG. 8, assigned to "Kind of Doc" allows the operator to set the font of a document. The key assigned to "Mag Change" is used to set a magnification for enlargement or reduction in accordance with a document size. The key, labeled 119, assigned to "Kind of Sheets" is used to select the kind of sheets 56. Further, the rightmost key assigned to "Position Adj" 15 allows the operator to adjust the position of an image to be printed on each sheet 56. Why only the key assigned to "Kind of Sheets" is labeled 119 is that the contents of operation available with the other keys are not relevant to the understanding of the illustrative embodiment.

20 The print mode picture shown in FIG. 8 appears on the LCD 114 first when a power switch, not shown, provided on the printer 200 is turned on.

25 An operation status or a message appears in the top rectangular column of the print mode picture; a message "Ready to make a master and print." is shown as appearing in the above column in FIG. 8,

showing the operator that the printer 200 is ready to execute the previously stated sequence. When the key 119 is pressed once, the lower portion of the print mode picture is replaced with a picture shown in FIG. 9. The picture of FIG. 9 includes "← (left arrow)", "→ (right arrow)", "Condition Change" and "Set" as named from the left to the right. A left key 117, a right key 118, a condition change key 120 and a set key 116 are respectively assigned to "←", "→", "Condition Change" and "Set" and constitute the select key group 115. The condition change key 120 allows the operator to select functions for changing sheet feed conditions relating to misfeed, overlap feed or similar defective sheet feed. This key 120 will not be described specifically because it does not lie in the scope of the present invention.

The key or kind-of-sheet setting means 119 allows the operator to set the kind of sheets 56 to use. The "←" key 117 also forms part of the kind-of-sheet setting means and causes, e.g., a function (job information) to be sequentially shifted to the left on the LCD 114. The "→" key 118 also forms part of the kind-of-sheet setting means and causes, e.g., the function (job information) to be sequentially shifted to the right on the LCD 114. The scroll keys 123 also form part of the kind-of-sheet setting means.

When the initial set key 122 is pressed once, a picture shown in FIG. 10 appears on the LCD 114.

As stated above, the scroll keys 123 and select key group 115 (set key 116, "←" key 117, "→" key 118 and kind-of-sheet key 119)

constitute the kind-of-sheet setting means for setting the kind of sheets 56. The initial set key 122, scroll keys 123 and select key group 115 (set key 116, "←" key 117 and "→" key 118) constitute sheet size setting means for setting the size of sheets 56.

5 The above kind-of-sheet setting means and sheet size setting means each are implemented by the combination of a plurality of keys appearing on a so-called menu picture. Alternatively, such setting means may be implemented by an independent key capable of displaying the size of sheets 56 selected via an LED (Light Emitting Diode) every
10 time it is pressed.

 Referring to FIG. 11, the controller or control means, labeled 50, is implemented as a microcomputer including a CPU (Central Processing Unit), I/O ports, a ROM (Read Only Memory), a RAM (Random Access Memory), a PROM (Programmable ROM), and a timer although not
15 shown specifically. These constituents of the microcomputer are interconnected by a signal bus. The ROM stores beforehand adequate sheet feed condition data to be described later and determined by, e.g., experiments, a program for operating the printer 200, etc. The RAM serves as a work area for storing, e.g., interim data.

20 The controller 50 adequately receives signals output from the temperature sensor 38, humidity sensor 39, pad sensors 41, switching sensors 25 and 26, angle sensor group 17, separation pressure position sensor group 8, keys (select key group 115 ("←" key 117, "→" key 118, kind-of-sheet key 119 and set key 116), initial set key 122 and scroll
25 keys 123), upper limit sensor 71, sheet size sensor group 57A, leading

edge sensor 83, sheet sensor 64, sheet feed position sensor 36, jump board angle sensor 37, overlap feed sensor 43, kind-of-sheet sensor 45, and print counter 47. In response, the controller 50 adequately controls the LCD 114, pad motor 23, angle motor 14, separation pressure motor 7, tray motor 59, feed pressure motor 75, jump board angle motor 93, air blower 84, sheet feed motor 66, and registration motor 82A. It is to be noted that blocks indicated by dash-and-dots lines in FIG. 11 are not used in this embodiment.

The controller 50 has the following various functions.

First, in response to signals output from the kind-of-sheet setting means (scroll keys 123 and select key group 115 (set key 116, "←" key 117, "→" key 118 and set key 116)), the controller causes the pad motor 23 to automatically select the separator pad 1 or 2 matching with the kind of the sheets 56.

Second, in response to signals output from the kind-of-sheet setting means (scroll keys 123 and select key group 115 (set key 116, "←" key 117, "→" key 118 and kind-of-sheet key 119)), the controller 50 causes the angle motor 14 to automatically switch the preset angle of the separator pad 1 or 2 to an angle matching with the kind of the sheets 56.

Third, in response to signals output from the temperature sensor 38 and humidity sensor 39, the controller 50 causes the pad motor 23 to automatically select the separator pad 1 or 2 in accordance with temperature, humidity and other environmental conditions.

Fourth, in response to signals output from the temperature

sensor 38 and humidity sensor 39, the controller 50 causes the angle motor 14 to automatically switch the angle of the separator pad 1 or 2 in accordance with temperature, humidity and other environmental conditions.

5 Fifth, when the overlap feed of the sheets 56 occurs more than a preselected number of times, as determined by the overlap feed sensor 43, the controller 50 causes the pad motor to automatically select a new separator pad 1 or 2.

10 Sixth, when the overlap feed of the sheets 56 occurs more than a preselected number of times, as determined by the overlap feed sensor 43, the controller 50 causes the angle motor 14 to automatically select the angle of the separator pad 1 or 2 matching with the frequency of overlap feed.

15 Seventh, when the separator pad 1 or 2 is to be automatically replaced, the controller 50 causes the separation pressure motor 7 to cancel the separation pressure and then causes the motor 7 to select a new separator pad 2 or 1.

20 Eighth, when the new separator pad 1 or 2 automatically selected is the last pad available, the controller 50 causes the LCD 114 to display a message indicative of the absence of spare pads via the LCD driver.

25 Ninth, when the new separator pad 1 or 2 is automatically selected, the controller 50 causes the separation pressure motor 7 to automatically select a separation pressure matching with the pad 1 or 2 and set up the separation pressure.

Tenth, when the new separator pad 1 or 2 is automatically selected, the controller 50 automatically selects and sets a feed pressure, an amount of feed and other sheet feed conditions matching with the pad 1 or 2. In this sense, the controller 50 plays the role of sheet feed condition control means. More specifically, in the illustrative embodiment, the controller 50 automatically selects a feed pressure, a separation pressure, a jump board angle and an amount of loop and controls the motors 75, 7, 93 and 66 in accordance with such sheet feed conditions. The amount of loop is representative of the amount of sheet feed, as will be described specifically later.

Eleventh, the controller or sheet feed condition control means 50 automatically selects and sets a sheet feed pressure, an amount of sheet feed and other sheet feed conditions in accordance with the angel of the separator pad 1 or 2 automatically selected. More specifically, in the illustrative embodiment, the controller 50 automatically selects a feed pressure, a separation pressure, a jump board angle and an amount of loop and controls the motors 75, 7, 93 and 66 in accordance with such sheet feed conditions.

As for the above tenth function, the controller 50 may automatically select at least one of the various sheet feed conditions matching with the separator pad 1 or 2 and control at least one of the motors 75, 7, 93 and 66 in accordance with the condition or conditions selected.

Also, as for the eleventh function, the controller 50 may automatically select at least one of the various sheet feed conditions

matching with the angle of the separator pad 1 or 2 and control at least one of the motors 75, 7, 93 and 66 in accordance with the condition or conditions selected.

The operation of the printer 200 will be described hereinafter.

5 When the operator turns on the power switch of the printer 200, the initial picture shown in FIG. 8 appears on the LCD 114 of the operation panel 110. The initial picture shows the content of a job to be performed by the operator in its upper portion ("Ready to make a master and print."), as stated earlier.

10 When the operator watching the LCD 114 presses the kind-of-sheet key 119, the picture of FIG. 9 appears on the LCD 114 in place of the initial picture. The picture of FIG. 9 includes five different kinds of sheets, i.e., "Standard", "Rough", "Thin", "Thick" and "Special". This allows the operator to select one of the five kinds
15 of sheets by using the kind-of-sheet setting means, i.e., the scroll keys 123 and select key group 115. With this configuration, it is possible to automatically select optimal one of the separator pads 1 (standard) and 2 (special) in accordance with the kind of sheets 56, to automatically set up an optimal angle of the pad 1 or 2 matching
20 with the kind of sheets 56, and to minutely set up optimal sheet feed conditions in accordance with the kind and angle of the pad selected. If this kind of setting is not necessary, there may be effected setting conforming to the previously stated functions available with the controller 50, as proved by trial manufacture and experiments.

25 In FIG. 9, "Standard", for example, representative of standard

sheets is not specific alone. In light of this, when the operator sets the kind of sheets 56 on the kind-of-sheet setting means, more specific contents of "Standard" are displayed at the same time and can be readily selected by the operator.

5 Usually, when the operator presses the kind-of-sheet key 119, "Standard" is highlighted in black. In this condition, the operator may press the scroll key 123c or 123a to shift the highlighted portion and then enter it on the set key 116. In FIG. 9, "Standard" is selected, and "High Quality", "Medium Quality" and "Recycled" representative of
10 more specific contents of "Standard" are displayed below "Standard" and headed by "Ex. (Example)". When "Thin" designating thin sheets is selected, "Thin" and "Thin *Noshigami*" will be displayed below "Thin" and also headed by "Ex.". This is also true with "Rough" and "Thick", as shown in FIG. 12 specifically. When the operator selects the kind
15 of sheets 56 and sets it on the set key 116, the controller 50 controls the various sections to automatically perform the following operation.

 The controller 50 selects one of the separator pads 1 (standard) and 2 (special) having a coefficient of friction optimally
20 matching with the kind of sheets 56 selected by the operator and temperature, humidity and other environmental conditions, as shown in FIG. 12 specifically. More specifically, the controller 50 controls the pad motor 23 while referencing the outputs of the kind-of-pad sensors 41, switching sensors 25 and 26, temperature
25 sensor 38 and humidity sensor 39. At the same time, the controller

50 controls the angle motor 14 in order to set up an optimal angle of the separator pad 1 or 2 selected while referencing the outputs of the angle sensor group 17, temperature sensor 38 and humidity sensor 39.

5 Specific sheet feed conditions shown in FIG. 12 are optimal values determined beforehand on the basis of, e.g., experimental data and stored in the ROM mentioned earlier.

 The controller 50 automatically selects an optimal feed pressure, an optimal separation pressure, an optimal jump board angle and an optimal amount of loop or sheet feed shown in FIG. 12 and matching with the kind of sheets 56 selected by the operator and the kind and angle of the pad. The controller 50 then drives the feed pressure motor 75 in order to set up the optimal feed pressure while referencing the output of the feed pressure sensor 36. Also, the
10 controller 50 drives the separation pressure motor 7 in order to set up the optimal separation pressure while referencing the output of the separation pressure position sensor group 8. Further, the
15 controller 50 drives the jump board angle motor 93 in order to set up the optimal jump board angle while referencing the output of the
20 jump board angle sensor 37. In addition, the controller 50 drives the sheet feed motor 66 in order to set up the optimal amount of loop. In this manner, the optimal sheet feed conditions are automatically set up in accordance with the kind of sheets 56 manually selected.

 The contents of FIG. 12 will be described more specifically.
25 Temperature (°C) and humidity (RH%) are related to the sheet

separating and feeding ability, as stated earlier. Generally, for standard sheets and rough sheets, the separator pad 1 with the standard pad 1a having a relatively great coefficient of friction is selected because overlap feed is apt to occur with such sheets. For
5 thin sheets, thick sheets and special sheets (envelopes), the separator pad 2 with the special pad 2a having a relatively small coefficient of friction is selected because thin sheets are likely to crease and fail to be fed and because thick sheets and special sheets are likely to peel, although overlap feed is rare with such
10 sheets. Of course, part of rough sheets is rarely subjected to overlap feed and low in rigidity and must be dealt with in the same manner as thin sheets.

Generally, when the separator pad is raised, i.e., when the pad angle relative to the horizontal plane is increased in FIG. 2B,
15 the overlap feed preventing effect is enhanced, but the load to act on the separation and conveyance of a sheet tends to increase. Conversely, when the pad angle relative to the horizontal plane is reduced in FIG. 2B, overlap feed is likely to occur. In light of this, medium to large pad angles ranging from 20° to 22° are selected for
20 standard sheets and rough sheets in order to obviate overlap feed. On the other hand, small to medium pad angles ranging from 18° to 20° are selected for thin sheets, thick sheets and special sheets in order to guarantee conveyance by minimizing the above load while reducing overlap feed. It should be noted that the pad angle is varied over
25 the range of from 10° to 35° , depending on the material of the pad.

Numerical values representative of feed pressures and separation pressures are substitute values set in accordance with the size of the actual feed pressure and separation pressure (gf/cm^2); the pressures increase with the increase of the numerical value.

5 Generally, in the standard environment (temperature of 23°C and humidity of 65 RH%), the feed pressure causes feed failure to occur if excessively low or brings about overlap feed if excessively high while the separation pressure causes feed failure to occur if excessively high or brings about overlap feed if excessively low.
10 These relations are also taken into account in setting the pressures of FIG. 12 based on experimental results.

The jump board angle is a substitute representative of the angle of the jump boards and may be either one of two angles "up" and "down" shown in FIG. 12. For standard sheets, the jump board angle
15 must be increased (up) for providing the sheet 56 with a certain degree of rigidity before discharging it. This is also true with rough sheets and thin sheets. For thick sheets and special sheets (envelopes), the jump board angle must be reduced (down) because the sheet 56 itself has certain rigidity or cannot be provided with
20 rigidity.

The amount of loop refers to the amount of feed of the sheet 56 to be effected after the leading edge sensor 83 preceding the registration rollers 81 and 82 has sensed the leading edge of the sheets 56. After the leading edge of the sheet 56 has abutted against
25 a position just ahead of the nip between the rollers 81 and 82, the

sheet 56 is fed by the above amount in order to maintain a preselected amount of loop. Numerical values listed in FIG. 12 each refer to the number of pulses sent to the sheet feed drive motor 66; the amount of loop increases with the increase of the number of pulses. The amount of loop may be set in terms of the amount of feed of the pick-up roller 62 or that of the separation roller 63 without resorting to the leading edge sensor 83.

As stated above, in the illustrative embodiment, the feed pressure, separation pressure, jump board angle and amount of loop are set in accordance with the kind and angle of the automatically switched separator pad as optimal sheet feed condition data and variably controlled, as shown in FIG. 12. For more delicate control, there may be additionally controlled the amount of rotation of the separator roller 63, paying attention to the slip of the roller 53 relating to the kind of the sheet 56, or the intensity of an air stream to be output from the air blower 84, paying attention to the roll-up of the sheet 56 relating to the kind of the sheet 56.

Hereinafter will be described a specific sheet selecting and setting procedure and a paper conveying and printing operation. Assume that temperature and humidity are 23°C and RH 65% (standard environment), respectively, that the sheets 56 used last time are standard sheets, and that the pad currently selected is the standard pad 1. Under these conditions, it will be seen from FIG. 12 that the feed pressure is "3", the separation pressure is "2", the jump board angle is "up", and the amount of loop is "28".

When the operator turns on the power switch and then the kind-of-sheet key 119 in the above environment, the picture of FIG. 9 appears on the LCD 114 including a message "Input the kind of sheets." Usually, "Standard" is highlighted as the kind of sheets 56. When
5 the operator desires to use, e.g., drawing paper (thick sheets) as the sheets 56, the operator shifts the highlighted portion to "Thick" by pressing the "→" key 118 or the key 123a included in the scroll keys 123 and then enters it on the set key 116. As a result, a message
10 "Ex. high quality paper above 135 kg, drawing paper, postcard or similar thick paper" appears in the lower portion of the LCD 114. This allows the operator to confirm that drawing paper belongs to the class of "Thick" sheets and enter "Thick" immediately.

When "Thick" is selected by the operator, the controller 50 selects "special" (separator pad 2) as the kind of an optimal pad in
15 accordance with the sheet feed condition data of FIG. 12, i.e., temperature ranging from 16° to 25°, humidity of 51 % or above, and "Thick" selected by the operator as the kind of sheets 56. In addition, the controller 50 selects an optimal pad angle of 18° for the separator pad 2. Subsequently, the controller 50 so controls the pad motor 23
20 as to automatically replace the separator pad 1 (standard) with the separator pad 2 (special) by referencing the outputs of the pad sensors 41, switching sensors 25 and 26, temperature sensor 38, and humidity sensor 39. Further, the controller 50 so controls the angle motor 14 as to automatically replace the pad angle of 22° assigned
25 to the separator pad 1 with the pad angle of 18° optimal for the

separator pad 2 by referencing the outputs of the angle sensor group 17, temperature sensor 38, and humidity sensor 39.

When the controller 50 replaces the separator pad 1 (standard) with the separator pad 2 (special), it controls the separation pressure motor 7 to cancel the separation pressure, i.e., to lower the pads 1a and 2a away from the rectangular holes 30a of the front wall 30. This insures smooth switching while protecting the pads 1a and 2a and separator roller 63 from damage.

The controller 50 automatically selects, based on the special pad 2 and optimal pad angle of 18°, more minute optimal sheet feed conditions which are the feed pressure of "3", separation pressure of "1", jump board angle "up", and amount of loop "21". To set up the above feed pressure, the controller 50 controls the feed pressure motor 75 by referencing the output of the feed pressure position sensor 36. To set up the above separation pressure, the controller 50 controls the separation pressure motor 7 by referencing the output of the separation pressure position sensor group 8. Further, to set up the above jump board angle, the controller 50 controls the angle motor 93 by referencing the output of the angle sensor 37. In addition, to set up the above amount of loop, the controller 50 controls the sheet feed motor 66. Consequently, the optimal sheet feed conditions are automatically set up in accordance with the kind of the sheets 56 selected by the operator.

Before or after the above sheet selection, the operator presses the start key 111. In response, the document reading

operation of the document scanning section 210 and the conventional master making and used master discharging operation occur in parallel. As a result, a new master 53 is wrapped around the print drum 51.

Also, before or after the sheet selection, the operator stacks
 5 the sheets (drawing paper in this cases) 56 on the tray 54 located at its lower limit position, as determined by the lower limit sensor 94. The operator then inputs a desired number of prints on the numeral keys 113 and then presses the print key 112. In response, the controller 50 drives the tray motor 59 in order to lift the tray
 10 54. When the top of the sheet stack 56 on the tray 54 contacts the pickup roller 62 and then pushes it up, the arm 68 is also raised. The arm 68 presses the feeler 71a of the upper limit sensor 71 and thereby turns on the sensor 71. In response to the resulting output of the upper limit sensor 71, the controller 50 stops driving the tray
 15 motor 59 and locates the tray 54 at a preselected level or sheet feed position necessary for printing. Thereafter, printing in a print mode occurs. If the operator's recognition that drawing paper belongs to the "Thick" class is objectively correct, then the first print and successive prints will be output under the previously stated
 20 optimal sheet feed conditions.

Subsequently, the print drum 51 starts rotating while the sheet feed motor 66 starts rotating the pickup roller 62. The pickup roller 62 pays out the top sheet 56 in the direction X. At the same time, the separator pad 2 and separator roller 63 cooperate to
 25 separate the top sheet 56 from the underlying sheets 56. The top

sheet 56 is surely fed out without a jam ascribable to feed failure or overlap feed because of the optimal sheet feed conditions (feed pressure of "3" and separation pressure of "1").

When several sheets 56 are fed from the tray 54, the pickup
5 roller 62 and therefore arm 68 is lowered. When the upper limit
sensor 71 turns off due to the lowering of the arm 68, the controller
50 drives the tray motor 59 in response to the resulting output of
the sensor 71. As a result, the tray 54 is again raised until the
upper limit sensor 71 turns on. In this manner, the tray motor 59
10 is selectively turned on or turned off in accordance with the ON/OFF
of the upper limit sensor 71, intermittently raising the tray 54 to
the sheet feed position.

When the leading edge of the sheet 56 paid out by the pickup
roller 63 abuts against a position just short of the nip between the
15 registration rollers 81 and 82, the sheet 56 forms a loop of the amount
of "21" corresponding to the number of pulses sent to the sheet feed
motor 66. Subsequently, the registration rollers 81 and 82 rotate
in synchronism with the rotation of the print drum 51, driving the
sheet 56 at a preselected timing. The sheet or print 56 on which an
20 image is printed at the nip between the print drum 51 and the press
roller 80 is driven out to the tray 87. At this instant, the jump
board angle "down" which is one of the optimal sheet feed conditions
provides the sheet 56 with an adequate degree of rigidity (not
effected with "Thick" sheets), so that the sheet 56 is neatly stacked
25 on the tray 87. Every time the print drum 51 makes one rotation, a

single sheet or print 56 is fed without a jam or similar trouble in conveyance, then printed with an image, and then discharged without a jam or similar trouble in conveyance. The above procedure is executed with a stencil printer not needing a printing step for
5 adhering a master to the print drum 51. A stencil printer needing such a step will produce a single print when the start key 111 is pressed, causing the master 53 to closely adhere to the print drum 51 due to the adhesion of ink.

Assume that the overlap feed sensor 43 senses overlap feed more
10 than a preselected number of times while the above printing operation is repeated. Then, the controller 50 controls the pad motor 23 in order to automatically replace the separator pad 1 or 2 with a new pad 1 or 2. In addition, the controller 50 controls the angle motor 14 for automatically selecting a preselected angle of the pad 1 or
15 2 matching with the frequency of overlap feed. At this instant, the controller 50 causes, e. g., a message "No spare pads; prepare new pads." to appear on the LCD 114, urging the operator to give an order for new pads. This successfully prevents the printer 200 from being killed over a long period of time due to the absence of new pads.

Referring to FIGS. 13, 14 and 15, an alternative embodiment
20 of the present invention will be described. As shown, a stencil printer, generally 300, includes a conventional press drum 306 in place of the press roller or pressing means 80 of the stencil printer 200. The press drum 306 has a sheet clamber or clamping means 307
25 for clamping the leading edge of the sheet 56. In this embodiment,

the controller 50 additionally controls the timing for the registration rollers 81 and 82 to convey the leading edge of the sheet 56 and the sheet conveying speed. As for the rest of the construction, the stencil printer 300 is essentially similar to the stencil printer 200.

The press drum 306 with the sheet clamber 307 has substantially the same outside diameter as the print drum 51. The press drum 306 rotates at substantially the same peripheral speed as, but in the opposite direction to, the print drum 51 while clamping the leading edge portion of the sheet 56 over 2 mm to 5 mm and forcibly peels off the leading edge portion from the print drum 51. With the press drum 306, it is possible to prevent the leading edge of the sheet 56 from remaining on the print drum 51 and rolling up without being peeled off by an air blower (air knife) and/or a peeler not shown in FIG. 13. It is also possible to reduce noise and to enhance the positional accuracy (registration accuracy) of an image in the direction X in which the sheet 56 is conveyed.

Clamping the leading edge portion of the sheet 56 obviates the following occurrence. So long as the sheet 56 is a relatively thin standard sheet, the sheet clamber 307 can easily clamp it. However, because the sheet clamber 307 has a layout shown in FIG. 14 in an exaggerated form, the clamber 307 cannot bend the leading edge portion of drawing paper, postcard or similar thick sheet inward or clamp it without resorting to a great clamping force. Then, the sheet clamber 307 fails to fully close its end portion and causes it spaced above

the periphery of the press drum 306 (indicated by a dash-and-dots line in FIG. 14) to hit against the master 53 wrapped around the print drum 51. The end of the sheet clamper 307 repeatedly hits against the same portion of the master 53 every time the press drum 306 rotates, causing the above portion of the master 53 to break. Consequently, the ink fed to the outer periphery of the print drum 51 is forced out through the broken portion of the master 53 and smears the sheet clamper 307 and therefore the leading edge portion of the sheet 56. Moreover, because such a master 53 is pulled to the upstream side in the direction of rotation of the ink drum 51 at each time of printing, it tears at the broken portion and is shifted to the upstream side in the above direction.

A main motor 303, not shown in FIG. 1, causes the print drum 51 to rotate in a direction indicated by an arrow in FIGS. 13 and 14.

The main motor 202, implemented by a DC motor by way of example, does not have to transfer its rotation to the sheet feed driveline and is therefore smaller in size than the conventional main motor. The main motor 303 drives the press drum 306 via a drive transmission mechanism, not shown, in addition to the print drum 51. An ink feeding device 301 is arranged in the print drum 51 and includes an ink roller and a doctor roller not shown in FIG. 1.

A recess 308 is formed in the periphery of the press drum 306 in order to prevent the sheet clamper 307 from contacting the clamper 52 of the print drum 51. Specifically, the sheet clamper 307 and a clamper base 309 are disposed in the recess 308. The sheet clamper

307 is openably mounted on the clamber base 309 via a shaft 307a. A spring, not shown, constantly biases the sheet clamber 307 toward a closed position. A cam, not shown, mounted on the printer body causes the sheet clamber 307 to open at a preselected timing, clamp the leading edge of the sheet 56, and then close to retain the sheet 56 on the press drum 306.

The press drum 306 identical in outside diameter with the print drum 51 accurately makes one rotation when the print drum 51 makes one rotation, causing the recess 308 to face the clamber 52. This allows the sheet clamber 307 to be mounted on the press drum 306 for clamping the leading edge of the sheet 56, as shown in FIG. 13. By feeding the sheet 56 while causing its leading edge to abut against the sheet clamber 307, it is possible to increase the registration accuracy of the sheet 56. More specifically, after the leading edge of the sheet 56 has abutted against the sheet clamber 307 held at a position shown in FIG. 13 (sheet clamp position), the clamber 307 is closed to clamp the leading edge. Subsequently, the sheet clamber 307 is sequentially moved counterclockwise due to the rotation of the press drum 306. At a position just before a peeler 320 (sheet unclamp position), the sheet clamber 307 is opened to release the leading edge of the sheet 56 at a position past of a press position where the ink is transferred to the sheet 56. As a result, the sheet 56 is prevented from rolling up together with the print drum 51 despite the viscosity of the ink.

A moving mechanism 319 causes the press drum 306 to selectively

move into or out of contact with the outer periphery of the ink drum 51. The moving mechanism 319 includes a pair of arms 312a and 312b respectively rotatably supporting shafts 313 affixed to opposite ends of the press drum 306. The arms 312a and 312b are respectively
5 rotatable about shafts 311a and 311b so as to angularly move the press drum 306. Cam followers, not shown, each are rotatably mounted on the other end of each arm 312a or 312b. A pair of springs 314a and 314b are respectively anchored to the arms 312a and 312b for constantly biasing the press drum 306 toward the print drum 51. A
10 pair of print cams, not shown, respectively selectively contact the above cam followers.

The sheet feeding section 240 is located at the right-hand side of the press drum 306 as in the previous embodiment. A drive mechanism around the registration motor 82A, not shown in FIG. 1, will
15 be described specifically. A drive pulley 321 is mounted on the output shaft of the registration motor 82A. A timing belt 333 is passed over the drive pulley 321 and a driven pulley 322 mounted on the shaft of the lower registration roller 82. In this configuration, the registration motor 82A causes the registration roller 82 to rotate
20 counterclockwise via the timing belt 333.

As shown in FIG. 13, two screen plates 315 and 316 are fastened to a front end wall 310 forming part of the press drum 306 by screws. The screen plates 315 and 316 are spaced from each other by a preselected distance in each of the radial and circumferential
25 directions of the press drum 306. Two transmission type photosensors

317 and 318 are fastened to the inner surface of the arm 312a by screws and spaced from each other by a preselected distance in the radial direction of the press drum 306.

5 The screen plate 315 blocks the optical path of the photosensor 317 when the press drum 306 is rotated counterclockwise to a preselected position. The screen plate 315 and photosensor 317 play the role of sheet feed timing sensing means for determining the timing for feeding the leading edge of the sheet 56 to the registration rollers 81 and 82.

10 The screen plate 316 blocks the optical path of the photosensor 318 when the press drum 306 is rotated counterclockwise to another preselected position. The screen plate 316 and photosensor 318 constitute timing sensing means for determining the timing for driving the leading edge of the sheet 56 toward the sheet clamber 307.

15 In addition, the screen plate 316 and photosensor 318 play the role of rotation position sensing means for sensing the position of the sheet clamber 307 in the circumferential direction of the press drum 306. Assume the distance on the sheet transport path between the nip between the registration rollers 81 and 82 and the position where the
20 leading edge of the sheet 56 abuts against the sheet clamber 307, and the circumferential distance between the angular position of the press drum 306 where the screen plate 316 meets the photosensor 318 and causes it to output an ON signal and the sheet clamber 307 against which the sheet 56 is abutting. Then, the screen plate 316 is
25 positioned on the end wall 310 such that the above two distances are

equal to each other.

When the sheet 56 is a thick sheet, the controller 50 varies the timing for feeding the sheet 56 toward the sheet clamber 307 such that the leading edge of the sheet 56 is fed to a position where it will not be clamped by the sheet clamber 307, and such that the leading edge is shifted to the upstream side in the direction X relative to the sheet clamber 307 by a preselected amount. More specifically, the controller 50 controls the registration motor 82A in response to the output of the photosensor 318 in such a manner as to delay the above sheet feed timing.

The master making section 220 includes a master conveying device including a platen roller, not shown, rotatable while pressing the master or stencil 53 against a conventional thermal head, not shown, and a pulse motor, not shown, for driving the platen roller. The thermal head has a number of heating elements. When the sheet 56 is a thick sheet, the controller 50 additionally controls the above pulse motor in such a manner as to delay the position where the thermal head starts making a master by the above delay of the sheet feed timing assigned to the registration motor 82A.

The above control over the master making section 220 and/or the open/close control over the sheet clamber 307 is not essential. Alternatively, the registration motor 82A may be controlled at substantially the same timing and rotation speed as when a standard sheet is fed to the top of the clamber 307 which is closed then or is constantly closed. This is also successful to obviate the

previously stated occurrence.

For details of the sheet feed control relating to the use of the press drum 306, reference may be made to Japanese Patent Laid-Open Publication No. 10-149091.

5 Specifically, the controller 50 controls the pad motor 23 by referencing the outputs of the pad sensors 41, switching sensors 25 and 26, temperature sensor 38 and humidity sensor 39 in order to automatically select the separator pad 1 (standard) or 2 (special) having an optimal coefficient of friction (see FIG. 12). At the same
10 time, the controller 50 controls the angle motor 14 in order to automatically set the optimal angle of the separator pad 1 or 2 by referencing the outputs of the angle sensor group 17, temperature sensor 38, and humidity sensor 39.

FIG. 15 lists specific sheet feed conditions identical with
15 the conditions of FIG. 12 except for the addition of "Paper Clamp" which was also determined by experiments. The conditions shown in FIG. 15 are stored in the ROM of the controller 50 as sheet feed condition data beforehand. The "Paper Clamp" refers to whether or not the sheet clamber 307 clamps the leading edge of the sheet 56 ("yes"
20 and "no" referring to clamping and not clamping, respectively). The clamber 307 clamps standard sheets, rough sheets and thin sheets belonging to a group of relatively thin sheets 56, but does not clamp thick sheets and special sheets belonging to a group of relatively thick sheets 56.

25 Another alternative embodiment of the present invention will

be described hereinafter. This embodiment is identical with the embodiment described with reference to FIGS. 1 through 12 except for the following. The illustrative embodiment includes a plurality of (two in the embodiment) separator pads 1 having the same coefficient of friction in place of the separator pads 1 and 2 different in the coefficient of friction. In the illustrative embodiment, the controller or control means 50 controls the pad motor 23 such that when the print counter 47 counts a preselected number of prints, the separator pad 1 in operation is automatically replaced with a new separator pad 1.

Specifically, the two separator pads 1 are respectively set on the two pad holder guides 3 of the pad switching section C. Assume that the print counter 47 reaches a preselected count during the repeated paper passing and printing operation as in the embodiment of FIGS. 1 through 12. Then, the controller 50 drives the pad motor 23 to automatically replace the separator pad 1 in operation with a new or spare separator pad 1. At this time, the previously mentioned specific message "No spare pads; prepare new pads." appears on the LCD 114, urging the operator to give an order for new pads. This embodiment not only achieves the same advantage as the previous embodiment, but also achieves an advantage that the time for replacing the separator pad 1 is extended because the pad 1 in operation is automatically replaced with a spare pad 1 without resorting to troublesome manual switching of the pads 1. It is to be noted that the controller 50 may execute the above control on the basis of the

number of prints driven out to the tray 87, FIG. 1.

A modification of the embodiment shown in FIGS. 1 through 12 includes a kind-of-sheet sensor 45 (indicated by a dash-and-dots line in FIG. 11) in place of the kind-of-sheet setting means of the previous embodiment. The sensor 45 is capable of determining the kind of sheet 56. Specifically, the sensor 45 may be an optical sensor responsive to the intensity of a reflection from the sheet 56 representative of the thickness of the sheet or an electrical sensor responsive to a mechanical gap between rollers also representative of the thickness of the sheet 56.

In the above modification, the controller 50 controls, based on the output of the kind-of-sheet sensor 45, the pad motor 23 in order to automatically select the separator pad 1 or 2 in accordance with the kind of the sheets 56. At the same time, the controller 50 controls the angle motor 14 in order to automatically set up the optimal angle of the separator pad 1 or 2 matching with the kind of the sheets 56.

Another modification of the embodiment shown in FIGS. 1 through 12 is characterized in that it sets up more desirable sheet feed conditions by taking account not only of the quality of the sheets 56 including thickness and surface condition, but also of the size of the sheets 56. That is, in this modification, the kind of the sheets 56 includes the sheet size as well.

The kind of the sheets 56 is manually selected and set via the kind-of-sheet setting means or automatically sensed and set via the

kind-of-sheet sensing means, as in the previous embodiment. Subsequently, while the LCD 114 is displaying the initial picture shown in FIG. 8, the operator presses the initial set key 122. As a result, the picture shown in FIG. 10 appears on the LCD 114 in place of the initial picture and shows a specific message "Input a sheet size." in its upper portion. Also, the picture of FIG. 10 shows three different classes of sheet size, i.e., A3 and B4, A4 and B5 and postcard on its second line from the top. This modification is capable of automatically selecting one of the three sheet sizes.

Specifically, this modification automatically senses the size of the sheets 56 with a sheet size sensing mechanism including the size sensor group 57A, FIGS. 7 and 11. Assume that the sheets 56 stacked on the tray 54 are standard sheets and have a size A3 or B4. Then, "A3, B4" included in the picture of FIG. 10 is highlighted to show that the sizes A3 and B4 are automatically selected. The operator watching the LCD 114 should only press the set key 116. In response, the controller 50 selects more desirable sheet feed conditions taking account of the sheet size as well, and so controls the various factors as to set up the more desirable sheet feed conditions. While such more desirable sheet feed conditions taking account of the sheet size are not shown specifically, they are stored in the ROM of the controller 50 in the same manner as the data listed in FIG. 12.

Generally, the more desirable sheet feed conditions taking account of the sheet size are selected in consideration of the

following and determined by experiments. The sheet feed pressure is increased for the sheets 56 of relatively great sizes A3 and B4 needing a great conveying force, but reduced for the sheets 56 of relatively small sizes A4 and B5 needing only a small conveying force. As for postcards, a feed pressure between the pressure assigned to A3 and B4 and the pressure assigned to A4 and B5 is selected, as indicated by experimental results.

The separation pressure is increased for the sheets 56 of relatively great sizes A3 and B4 in order to obviate overlap feed, but reduced for the sheets 56 of relatively small sizes A4 and B5. As for postcards, a separation pressure even lower than the pressure assigned to A4 and B5 (corresponding to a numerical value of 1), as indicated by experimental results.

The jump board angle must be increased for the sheets 56 of sizes A4 and B5 in order to provide the sheets 56 with a sufficient degree of rigidity. This is also true with the sheets 56 of sizes A3 and B4. However, the jump board angle must be reduced for postcards because postcards themselves have rigidity or cannot be provided with rigidity.

The above automatic sheet size sensing using the sheet size sensing mechanism including the sensor group 57A is not essential. Alternatively, the operator may select and set a sheet size on the initial set key 122, scroll keys 123 and select key group 115 (set key 116, "←" key and "→" key) constituting the sheet size setting means. For example, when the operator stacks the sheets 56 of size

A4 or B5 on the tray 54, "A3, B4" is initially highlighted to indicate the sheet size. In this condition, the operator may shift the highlighted portion by using the key 117 or 118 or the key 123c or 123a and then enter it on the set key 116.

5 If the above control taking account of more minute sheet feed conditions is not necessary, the kind-of-sheet setting means and kind-of-sheet sensing means may be replaced with the setting of sheet feed conditions considering a difference in sheet size only. Again, the kind of the sheets 56 includes the sheet size. In this case, the
10 operator does not set the kind of the sheets 56, but presses the initial set key 122 in the condition shown in FIG. 8 in order to select a sheet size in the previously stated manner, or the sheet size sensing mechanism including the size sensor group 57A automatically senses the sheet size.

15 The foregoing description has concentrated on the problems relating to separating members implemented as separator pads. A system including a plurality of separator rollers or similar sheet separating means and a plurality of pickup rollers or similar sheet feeding means, automatically switching them in accordance with the
20 kind of sheets and environmental conditions and automatically setting optimal sheet feeding means also lies in the scope of the present invention.

 In summary, it will be seen that the present invention provides a sheet feeding device for an image forming apparatus having various
25 unprecedented advantages, as enumerated below.

(1) A particular separating member and a particular angle of the separating member can be automatically selected. This makes it needless for the operator to change sheet feed conditions by relying on experiences. Optimal sheet feed conditions are automatically selected and insure stable sheet feed.

(2) A particular separating member and a particular angle of the separating member can be automatically selected in accordance with the kind of sheets to be used. This also frees the operator from troublesome manual setting and insures stable sheet feed under optimal sheet feed conditions.

(3) A particular separating member and a particular angle of the separating member can be automatically selected in accordance with temperature, humidity and other environmental conditions. This also frees the operator from troublesome manual setting and insures stable sheet feed under optimal sheet feed conditions.

(4) A separating member in operation can be automatically replaced with a spare separating member. This frees the operator from manual replacement and extends the time for replacement.

(5) Inadequate separation conditions ascribable to the wear of the separating member are obviated which would lead to defective sheet feed.

(6) The separating member and, e.g., a separator roller cooperating to generate a separation pressure are protected from damage due to the contact condition thereof.

(7) The time for giving an order for new separating members

can be accurately determined. It is therefore possible to surely obviate the waste of time ascribable to the absence of separating members and to prevent the apparatus from being killed over a long period of time.

5 (8) A separation pressure can be automatically selected and set up as an optimal sheet feed condition. This further promotes stable sheet feed.

10 (9) A feed pressure and an amount of feed can be automatically selected and set up as optimal sheet feed conditions, further promoting stable sheet feed.

 (10) It is not necessary for the operator to manually set the kind of sheets to be used. The kind of sheets can therefore be surely determined without any troublesome operation or errors ascribable thereto.

15 (11) The operator is allowed to set the kind of sheets to be used.

20 (12) It is not necessary for the operator to manually set a sheet size. Optimal sheet feed conditions can therefore be automatically switched without any troublesome operation or errors ascribable thereto.

 (13) The operator is allowed to set a sheet size. Optimal sheet feed conditions can therefore be automatically switched.

 (14) The device is most advantageous from the structure and cost standpoint.

25 Various modifications will become possible for those skilled

in the art after receiving the teachings of the present disclosure without departing from the scope thereof.

100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2